

```
#####
# The Fixed Path Vehicle Refueling Problem
# MATH 333, Operations Research.
# Note by Dr. Shieu-Hong Lin
#####
```

```
#####
# 1. Description of the generic model
#####
```

The vehicle starts at the location of the fuel station S_1 and travels along a fixed path that passes through the fuel stations $S_1, S_2, \dots, S_{N-1}, S_N$ in order. The fuel station S_N is the very last fuel station before reaching the final destination.

Parameters

- Tank capacity of the vehicle (in gallons).
- The initial amount of fuel in the tank of the vehicle (in gallons).
- N : the number of the stations (stations S_1, S_2, \dots, S_N) on a given fixed path.
- For each j in 1 to N , we have the following additional information associated with station S_j
 - c_j : the fuel cost per gallon at the j th station S_j .
 - g_j : the amount of fuel consumed (in gallons) to go from station S_j to the next station (or to the final destination from the very last station S_N).

Decision to make at station S_j

- Y_j : the amount of fuel to fill in at station S_j .
- If Y_j is 0, it means the vehicle simply passes by without refueling at station S_j .
- **Note that** (i) you can never refuel the tank to go beyond the tank capacity and (ii) when you leave station S_j , you should have enough fuel to reach the next station (or to reach the destination when leaving S_N).
- **A feasible refueling policy** $\langle Y_1, Y_2, \dots, Y_N \rangle$ **ensures** that the amount of fuel in the tank should never go below 0 and should never go beyond the tank capacity throughout the entire trip.
- **An optimal refueling policy** $\langle Y_1, Y_2, \dots, Y_N \rangle$ **is a feasible refueling policy that minimizes the total fuel cost.**

Relevant and useful variables you may also consider in the context of station S_j

- X_j : the amount of fuel in the tank when the vehicle just arrives at station S_j without doing any refueling operation there.
- Z_j : the amount of fuel in the tank when the vehicle is going to leave station S_j (possibly after a refueling operation there).
- **Note that** (i) X_1 is determined by the initial amount of fuel in the tank of the vehicle, (ii) Z_j is determined by X_j and Y_j , and (iii) X_{j+1} is determined by Z_j and g_j .

Operational objective:

Determine Y_j (the amount of fuel to fill in at station S_j) for each j in 1 to N to minimize the total the fuel cost subject to the constraints that the amount of fuel in the tank should never go below 0 and should never go beyond the tank capacity. In other words, **determine an optimal refueling policy $\langle Y_1, Y_2, \dots, Y_N \rangle$ for the trip.**

#####

2. Data section

#####

data;

Let the tank capacity be 10.

Let the initial fuel amount be 0.

Let N be 3. In other words, three stations.

Let the coefficients c_j and g_j be

for $j=1$, 2 5

for $j=2$, 4 9

for $j=3$, 3 7;